



5.8 GHz ISM / UNII Band 12 dBi Professional Omnidirectional Wireless LAN Antenna - Model: HG5812U-PRO

Applications and Features

- Applications:**
- 5.8GHz UNII and ISM applications
 - 5.8GHz Wireless LAN systems
 - WiFi
 - Multipoint Applications

- Features:**
- Superior performance
 - Heavy duty industrial grade design
 - All weather operation
 - DC Ground lightning protection
 - Integral N-Female Connector
 - Supplied with mast mounting kit
 - RoHS Compliant



Description

Professional Performance

The HyperGain® HG5812U-PRO is a professional high gain omni-directional base station WiFi antenna designed and optimized for the 5.8GHz ISM and UNII band. This antenna is ideally suited for multipoint applications where long range and wide coverage is desired.

Rugged and Weatherproof

The HG5812U-PRO construction features a heavy-duty fiberglass radome for durability and aesthetics. Designed to operate in the harshest of environments, the HG5812U-PRO far exceeds other omni-directional antennas. The included mounting system features heavy-duty mast clamps, allowing installation on masts from 1.4 inches (35 mm) up to 2.0 inches (50 mm) diameter. This antenna features an integral N-Female connector.


Specifications

Electrical Specifications

Frequency	5725-5850 MHz
Gain	12 dBi
Polarization	Vertical
Downtilt	0°
Vertical Beam Width	6°
Horizontal Beam Width	360°
Impedance	50 Ohm
Max. Input Power	150 Watts
VSWR	< 1.5:1 avg.
Lightning Protection	DC Short


Mechanical Specifications

Weight	1.5 lbs (0.7kg)
Length	29.4 in. (0.7 m)
Base Diameter	2.28 in. (57.9mm)
Radome Diameter	2.04 in. (51.8mm)
Radome Material	Fiberglass
Mounting	1.4 in. (35 mm) to 2.0 in. (50 mm) dia mast
Rated Wind Velocity	137 MPH/S (220Km/S)
Operating Temperature	-40° C to to 85° C (-40° F to 185° F)
Connector	Integral N-Female
RoHS Compliant	Yes

RF Antenna Patterns

Guaranteed Quality

This product is backed by Hyperlink's Limited Warranty.